

厨房设备技术规范要求

KITCHEN EQUIPMENT SPECIFICATION-GENERAL SPECIFICATION

第二部分：材料要求

Part-2 Material

第一章：设备

Chapter-1 Equipment

本章节所描述的设备技术规格若与设备特殊技术要求章节不符，以后者所规定的要求为准。

In case of any discrepancy found between this chapter and particular specifications be subject to latter.

1. 厂制品 Fabrication

1.1 工作台、活动工作台、设备架和星盆工作台 (后场):

Worktable/Mobile Table/Equipment Stand/Sink (B.O.H.)

- | | | | |
|----|---|----------------------|--|
| a. | 台面 Tabletop | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| b. | 台面和下层板加强筋 Reinforcement | 2.0mm±5% 12 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| c. | 下层板 Undershelves | 1.2mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| d. | DN50mm 脚杯 DN2" Leg Cup | 2.0mm±5% 12 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| e. | DN38mm 支撑脚 DN1-1/2" Leg | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| f. | DN20mm 横通 DN 3/4" Crossbraising | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| g. | 子弹脚-NSF 认可的不锈钢材料；圆柱形脚趾；最大圈外径 40mm-42mm；承重力不小于 850kg；高度可调节范围不小于 30mm。 Bullet foot-NSF approved S/S, cylindrical foot, DN1-3/4" outer ring, 850Kg loading, adjustable range no less than 1-1/4 ". | | |
| h. | 5" 脚轮-外径 5" 的万向轮；承重力不小于 90kg；灰色聚亚安酯橡胶轮；橡胶厚度不小于 30mm；带润滑油加油嘴和密封盖；带可拆卸式的固定底板。 DN5" Outer ring universal wheel, 90Kg loading, Polyurethane dark gray, min. thickness no less than 1-1/4" , with filling noodle & lid for lubricating oil, with removal bottom fixing panel. | | |
| i. | 星盆 Sink Basin | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| j. | 插盘架 Pan Slide | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |

1.2 工作柜、高身柜、星盆工作柜 (后场):

Work counter/With Sink/Upright Cabinet (B.O.H.)

- | | | | |
|----|---|----------------------|--|
| a. | 台面 Tabletop & Bottom | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| b. | 台面和下层板加强筋 Reinforcement | 2.0mm±5% 12 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| c. | 下层板 Undershelves | 1.2mm±5% 16 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| d. | 侧板 Lateral Panel | 1.2mm±5% 16 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| e. | 背板 Rear Panel | 1.2mm±5% 16 Gauge | 30418/8 不锈钢 Stainless Steel 304 18/8 |
| f. | DN40mm 脚连子弹脚 | | NSF 认可的不锈钢材料；六角形脚趾；承重力不小于 850kg；高度为 150mm 左右；可调节范围不小于 40mm；带可拆卸式的固定底板。 Bullet foot-NSF approved S/S, hexagonal foot, 850Kg loading, 6" high, adjustable range no less than 1-1/2 " , with removable bottom plate. |
| g. | 星盆 Sink | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| h. | 柜门 Door Panel | 1.2mm±5% 16 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| i. | 抽屉 Drawer Runner | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| j. | 抽屉导轨-全不锈钢或镀锌钢等防腐蚀材料制成；承重力不小于 45kg；带自动关闭；带阻尼；静音导轨；导轨便于清洁、易于维护。 Drawer Runner-Made of anticorruption material such as stainless steel or galvanized steel, 45kg loading, self-closing with , silent rail, easy to clean an maintain. | | |
| k. | 抽屉锁或锁扣-全 304 18/8 不锈钢；带两把金属钥匙。 Drawer Locker-304 stainless steel housing, with 2 keys. | | |
| l. | 移门导轨 Door Runner | 2.0mm±5% 12 Gauge | 304 18/8 不锈钢 304 18/8 Stainless Steel |
| m. | 移门滚轮-全 304 18/8 不锈钢；带不锈钢滚珠轴承；不锈钢固定螺栓。 Door Wheel-all 304 stainless steel parts | | |
| n. | 门铰链-可采用顶/底部固定式或排铰，全 304 18/8 不锈钢组件，单扇门用的铰链总承重力不小于 150kg。 Hinge-Using shaft hinges or barrel hinges, all parts shall be made of stainless steel, min. loading shall be no less than 150Kg. | | |

1.3 洗手星连下柜

Hand sink with cabinet

- | | | | |
|----|---------------|----------------------|--|
| a. | 外壳 Housing | 1.2mm±5% 16 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |
| b. | 星盆 Basin | 1.5mm±5% 14 Gauge | 304 18/8 不锈钢 Stainless Steel 304 18/8 |

1.4 推车类:

Trolley/Cart

- | | | | |
|----|------------|----------|--------------|
| a. | 40*40mm 方通 | 2.0mm±5% | 304 18/8 不锈钢 |
|----|------------|----------|--------------|

| | | | |
|-----|--|----------|--------------------------|
| | 40*40mm Tube | 12 Gauge | Stainless Steel 304 18/8 |
| b. | 底板 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Bottom Plate | 14 Gauge | Stainless Steel 304 18/8 |
| c. | 底板加强筋 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Reinforcement | 12 Gauge | Stainless Steel 304 18/8 |
| d. | 锁杆支架 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Lock Stick Bracket | 12 Gauge | Stainless Steel 304 18/8 |
| e. | DN15 锁杆 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Lock Stick | 14 Gauge | Stainless Steel 304 18/8 |
| f. | 护角片-耐高温人造树脂材料; 耐高温极限为-43°C to 230°C。 Corner Guard-made of heat resistant ABS, melting limit temperature 109°F~446°F. | | |
| g. | 插盘架 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Pan slide | 14 Gauge | Stainless Steel 304 18/8 |
| h. | 耐高温脚轮-4" 或 5" 轮, 耐高温人造树脂材料, 耐高温极限为-43°C to 230°C Heat resistant Wheel-4" ~5" , made of heat resistant ABS, melting limit temperature 109°F~446°F. | | |
| 1.5 | 挂墙架、墙柜, 天花吊架、吊柜, 坐台架、台柜 (后场): Wall/Ceiling hung/Countertop shelf/ cabinet (B.O.H.) | | |
| a. | 顶板和底板 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Top & Bottom Plate | 14 Gauge | Stainless Steel 304 18/8 |
| b. | 顶板加强筋 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Reinforcement | 12 Gauge | Stainless Steel 304 18/8 |
| c. | 隔板 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Mid-shelf | 14 Gauge | Stainless Steel 304 18/8 |
| d. | 挂墙架支架 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Wall Shelf Bracket | 12 Gauge | Stainless Steel 304 18/8 |
| e. | DN25mm 吊杆/支架 | 1.5mm±5% | 304 18/8 不锈钢 |
| | DN25mm Rod | 14 Gauge | Stainless Steel 304 18/8 |
| f. | 柜门 | 1.2mm±5% | 304 18/8 不锈钢 |
| | Door Panel | 16 Gauge | Stainless Steel 304 18/8 |
| g. | 移门导轨 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Door Runner | 12 Gauge | Stainless Steel 304 18/8 |
| h. | 移门滚轮-全 304 18/8 不锈钢; 带不锈钢滚珠轴承; 不锈钢固定螺栓。 Door Wheel-all 304 stainless steel parts | | |
| i. | 门铰链-可采用顶/底部固定式或排铰, 全 304 18/8 不锈钢组件, 单扇门用的铰链总承重力不小于 150kg。 Hinge-Using shaft hinges or barrel hinges, all parts shall be made of stainless steel, min. loading shall be no less than 150Kg. | | |
| j. | 墙体固定夹 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Wall Clip | 12 Gauge | Stainless Steel 304 18/8 |
| k. | 墙体固定槽 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Wall fixture | 12 Gauge | Stainless Steel 304 18/8 |
| l. | 柜底灯箱片 | 3.0mm±5% | 半透明白色亚克力板 |

| | | | |
|----|--|----------|------------------------------|
| | Light Film | 3.0mm±5% | Translucent or white acrylic |
| m. | LED 灯管/底座 色温 4000K; 白色冷光; 亮度不小于 200Lux; 寿命不小于 20000 小时; 额定功率 25~60W。 LED Light-4000k, 200Lux, 20000Hours lifelong span, 25~60w. | | |

1.6 地沟连盖板:

| | | | |
|----|--------------------------|----------|--------------------------|
| | Floor Trough and Grating | | |
| a. | 地沟篦子 | 1.5mm±5% | 316 不锈钢 |
| | Housing | 14 Gauge | Stainless Steel 316 |
| b. | 地沟盖板 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Grating | 12 Gauge | Stainless Steel 304 18/8 |
| c. | 排水口隔渣栏 | 1.0mm±5% | 316 不锈钢 |
| | Filtering Basket | 18 Gauge | Stainless Steel 316 |

1.7 集气罩、油网烟罩、运水烟罩和紫外线烟罩 (后场):

| | | | |
|----|--|-----------------|--------------------------|
| | Condensate/Grease/Water Washing/UV Hood (B.O.H.) | | |
| a. | 壳体 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Housing | 14 Gauge | Stainless Steel 304 18/8 |
| b. | 排烟口支管和法兰 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Vent Duct & Flange | 14 Gauge | Stainless Steel 304 18/8 |
| c. | 补分口支管和法兰 | 1.5mm±5% | 304 18/8 不锈钢 |
| | M.U.A. Duct & Flange | 14 Gauge | Stainless Steel 304 18/8 |
| d. | 支管保温材料 | 双层不锈钢 | 中空 10mm |
| | Duct Insulation | Double deck S/S | 10mm Thick Cavity |
| e. | 普通油网板-铝合金材质; 罩面尺寸在 500mm*500mm 左右; 每块重量不超过 4.5kg; 对于 3-10um 粒径的油烟粒子, 净化效率不低于 85%; 压损不超过 110Pa。 Grease Filtering Panel-made of aluminum, size of each piece no larger than 20" *20" , the weight of each piece no heavier than 4.5kg, the purification efficiency is not less than 85% for 3-10um particle sized oil and the pressure drop is no more than 110Pa. | | |
| f. | 紫外线油网板-铝合金材质; 罩面尺寸在 500mm*500mm 左右; 每块重量不超过 7.0kg; 对于 3-10um 粒径的油烟粒子, 净化效率不低于 85%; 压损不超过 117Pa; 完全遮挡紫外线的外泄。 Grease Filtering Panel-made of aluminum, size of each piece no larger than 20" *20" , the weight of each piece no heavier than 7.0kg, the purification efficiency is not less than 85% for 3-10um particle sized oil and the pressure drop is no more than 117Pa. | | |
| g. | 紫外线灯管-灯管为欧美全进口; 灯管为人造石英材质; 管长从 700mm-1700mm 可自由根据烟罩长度组合; 设计风速为 2M-2.5M/秒; 灯管组件包括全进口镇流器; 净化效率不低于 90%; 灯管功率不小于每米 35w。 UV Light-light tube must be imported, made of synthetic quartz, 28"-67" long based on the length of hood, designed velocity 2m~5m/sec., with imported ballast, the purification efficiency is not less than 90%, min. power of the light tube no less than 35w/m. | | |
| h. | 紫外线灯管支架 | 1.5mm±5% | 304 18/8 不锈钢 |
| | UV light bracket | 14 Gauge | Stainless Steel 304 18/8 |
| i. | 新风口百叶-根据设计图尺寸定加工或采购; 不锈钢或塑料材质; 可拆卸。 M.U.A. Louver-to purchase or fabricate based on the designed dimension, removable, made of stainless steel. | | |
| j. | 顶部封板 | 1.2mm±5% | 304 18/8 不锈钢 |

| | | | |
|------------|--|----------|--------------------------|
| | Top Closure Panel | 16 Gauge | Stainless Steel 304 18/8 |
| 1.8 烟罩控制箱: | Hood Control Panel | | |
| a. | 箱体 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Housing | 14 Gauge | Stainless Steel 304 18/8 |
| 1.9 加热元件: | Heating Elements | | |
| a. | 干发热管-304 18/8 不锈钢; 长度可定制; 管径 20mm-25mm; 单管功率 (500mm 长) 不小于 2.5kw; 220v 或 380v 额定电压; 使用寿命不小于 10000 小时。 Dry Heating-made of Stainless Steel 304 18/8, custom size & DN3/4" ~1" , min. power of each tube no less than 2.5kw/20 " , either 1 or 3 phase, lifelong span no less than 10000 hours. | | |
| b. | 出口/回风面板 | 1.2mm±5% | 304 18/8 不锈钢 |
| | In/out let Panel | 16 Gauge | Stainless Steel 304 18/8 |
| c. | 湿发热管-316 不锈钢; 长度可定制; 管径 20mm-25mm; 单管功率 (500mm 长) 不小于 2.5kw; 220v 或 380v 额定电压; 使用寿命不小于 10000 小时。 Wet Heating-made of Stainless Steel 316, custom size & DN3/4" ~1" , min. power of each tube no less than 2.5kw/20 " , either 1 or 3 phase, lifelong span no less than 10000 hours. | | |
| 1.10 其他设备: | Other Equipment | | |
| a. | DN25mm 托盘架 | 1.5mm±5% | 304 18/8 不锈钢 |
| | DN1" Tray Side | 14 Gauge | Stainless Steel 304 18/8 |
| b. | 托盘架支架 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Tray Slide Bracket | 12 Gauge | Stainless Steel 304 18/8 |
| c. | DN25mm 挂锅架 | 1.5mm±5% | 304 18/8 不锈钢 |
| | DN1" Pot Rack | 14 Gauge | Stainless Steel 304 18/8 |
| d. | 挂锅架支架 | 2.0mm±5% | 304 18/8 不锈钢 |
| | Pot Rack Bracket | 12 Gauge | Stainless Steel 304 18/8 |
| c. | 踢脚板 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Kick Plate | 14 Gauge | Stainless Steel 304 18/8 |

2. 制冷设备 Refrigeration Equipment

2.1 冷库

Walk-in Cooler

| | | | |
|----|-------------------------------|----------|--------------------------|
| a. | 外露面库板外侧板材 | 0.8mm±5% | 304 18/8 不锈钢 |
| | Exposed Panel Surface Outside | 20 Gauge | Stainless Steel 304 18/8 |
| b. | 非外露面库板外侧板材 | 0.6mm±5% | 白色彩钢板 |
| | Hidden Panel Surface Outside | 22 Gauge | White coated steel |
| c. | 库内饰面立板板材 | 0.8mm±5% | 白色彩钢板 |
| | Exposed Panel Surface Inside | 22 Gauge | White coated steel |
| d. | 顶板内外饰面板材 | 0.6mm±5% | 白色彩钢板 |
| | Top Panel | 22 Gauge | White coated steel |
| e. | 底板内外侧板材 | 1.5mm±5% | 镀锌板 |
| | Bottom Panel | 14 Gauge | White coated steel |

| | | | |
|----|---|----------|--------------------|
| f. | 外露面库板外护墙板 | 2.0mm±5% | 压花铝合金 |
| | Wall Protection Outside | 12 Gauge | Embossed aluminum |
| g. | 库内底板敷完成饰面 | 3.0mm±5% | 压花铝合金 (无安装基坑) |
| | Finished Floor | 8 Gauge | Embossed aluminum |
| | In the case of be without installation sunken floor. | | |
| h. | 冷库库板内圆角不允许内圆角弧形封板, 必须是冷库弧形角板 The sanitizing curve shall be part of the corner pieces of the panels formed integrally. | | |
| i. | 库门外立面板材 | 0.8mm±5% | 白色彩钢板 |
| | Cooler Door Outside | 22 Gauge | White coated steel |
| j. | 库门铰链-304 18/8 不锈钢; 带高强度弹簧自动回归功能; 开门角度不小于 100°; 每扇门安装 3 组门铰链 Door Hinge-made of stainless steel 18/8, self-closing, opening angle no less than 100° , provide 3 hinges for each door. | | |
| k. | 库门把手和门锁-304 18/8 不锈钢高光处理, 门内装有安全锁可由内部打开, 以便开启逃生 Lock-made of polished stainless steel 18/8, with safety unlock device inside cooler. Easily disable the lock and escaped from inside in case of get trapped. | | |
| l. | 顶部卡箍件-主体 304 18/8 不锈钢, 带密封件 Door Closer-made of stainless steel 18/8, with sealant. | | |
| m. | 隔热保温填-100mm 厚 100% 硬质聚氨酯或聚异氰脲酸酯隔热物质; 导热系数:≤0.022W/m²·K; 表观芯密度:≥40KG/立方米 Insulation foaming-4" thickness Polyurethane or Polyisocyanuric foamed (PU or PIR), Thermal Conductivity no larger than 0.022W/m²·K, density no less than 40KG/M³. | | |
| n. | 平衡窗-装置应附加加热设备, 以避免结霜及防潮。 Pressure Relief Port-with heater to prevent from frosting. | | |

2.2 工作台冰箱

Countertop Refrigerator

| | | | |
|----|---|--------------------------|--------------------------|
| a. | 台面板材 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Countertop | 14 Gauge | Stainless Steel 304 18/8 |
| b. | 侧板/背板 | 1.2mm±5% | 304 18/8 不锈钢 |
| | Lateral/Rear | 16 Gauge | Stainless Steel 304 18/8 |
| c. | 底板板材 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Bottom panel | 14 Gauge | Stainless Steel 304 18/8 |
| d. | 门板 | 1.2mm±5% | 304 18/8 不锈钢 |
| | Door Panel | 16 Gauge | Stainless Steel 304 18/8 |
| e. | 门铰链-顶部、底部安装式; 全 304 18/8 不锈钢组件, 单扇门用的铰链总承重力不小于 80kg; 带自动回归功能。 Hinge-shaft hinges, made of stainless steel 304 18/8 , min. loading no less than 80KG, self-closing. | | |
| f. | 抽屉导轨 | 304 18/8 不锈钢 | |
| | Drawer Runner | stainless steel 304 18/8 | |
| g. | 插盘架 | 1.5mm±5% | 304 18/8 不锈钢 |
| | Pan Slide | 14 Gauge | Stainless Steel 304 18/8 |
| h. | 冷媒介质-高温冰箱采用无 CFC 的环保雪种(R-134a); 低温冰箱采用无 CFC 的环保雪种(R-404a)。 Refrigerant-CFC free, R-134a for refrigerators and R-404a for freezers. | | |

- i. 隔热保温填充 厚 75mm 环保 PU 绝缘材料
Insulation 75mm thick Environmental PU foamed
- 2.3 高身冰箱
Upright Refrigerator
 - a. 面板 1.5mm±5% 304 18/8 不锈钢
Front Panel 14 Gauge Stainless Steel 304 18/8
 - b. 侧板/背板 1.2mm±5% 304 18/8 不锈钢
Lateral/Rear 16 Gauge Stainless Steel 304 18/8
 - c. 底板板材 1.5mm±5% 304 18/8 不锈钢
Bottom panel 14 Gauge Stainless Steel 304 18/8
 - d. 门板 1.5mm±5% 304 18/8 不锈钢
Door Panel 16 Gauge Stainless Steel 304 18/8
 - e. 门铰链-顶部、底部安装式; 全 304 18/8 不锈钢组件, 单扇门用的铰链总承重力不小于 80kg; 带自动回归功能。
Hinge-shaft hinges, made of stainless steel 304 18/8, min. loading no less than 80KG, self-closing
 - f. 插盘架 1.5mm±5% 304 18/8 不锈钢
Pan Slide 14 Gauge Stainless Steel 304 18/8
 - g. 冷媒介质-高温冰箱采用无 CFC 的环保雪种(R-134a); 低温冰箱采用无 CFC 的环保雪种(R-404a)。
Refrigerant-CFC free, R-134a for refrigerators and R-404a for freezers.
 - h. 隔热保温填充 厚 75mm 环保绝缘材料
Insulation 75mm thick Environmental PU foamed
- 2.4 前场冰箱/展示柜
Refrigerator (F.O.H.)
 - a. 台面板材 1.2mm±5% 304 18/8 不锈钢
Countertop 16 Gauge Stainless Steel 304 18/8
 - b. 侧板/背板 1.0mm±5% 304 18/8 不锈钢
Lateral/Rear 18 Gauge Stainless Steel 304 18/8
 - c. 底板板材 1.2mm±5% 304 18/8 不锈钢
Bottom panel 16 Gauge Stainless Steel 304 18/8
 - d. 门板 1.2mm±5% 304 18/8 不锈钢
Door Panel 16 Gauge Stainless Steel 304 18/8
 - e. 隔板 1.2mm±5% 304 18/8 不锈钢
Shelf 16 Gauge Stainless Steel 304 18/8
 - f. 玻璃 (单层) 12mm、8mm、3mm; 钢化玻璃; 超白玻璃;
Glass (Single Layer) 12mm, 8mm, 3mm tempered & ultra-clear glass
 - g. 玻璃 (中空双层) 5+6A+5mm, 6+9A+6mm; 钢化玻璃; 超白玻璃;
Glass (Double Layers) 5+6A+5mm, 6+9A+6mm tempered & ultra-clear glass
 - h. 玻璃 (单层+电热丝) 12mm、8mm、钢化玻璃; 超白玻璃;
Glass (Single Layer with Heater) 12mm, 8mm tempered & ultra-clear glass
 - i. 玻璃 (中空+电热丝) 5+6A+5mm, 6+9A+6mm; 钢化玻璃; 超白玻璃;
Glass (Double Layers with Heater) 5+6A+5mm, 6+9A+6mm tempered & ultra-clear glass
 - j. 玻璃边框-0.6mm±5% 304 18/8 不锈钢, 完成面、颜色由室内设计指定, 见设备特殊要求章节。
Glass Frame-22 Gauge stainless steel 304 18/8, finish and color to be specified by I.D. Refer to

- the Particular specification for more details
 - k. 底部不可见面柜体 1.2mm±5% 304 18/8 不锈钢
Hidden Bottom Plate 16 Gauge Stainless Steel 304 18/8
 - l. 所有可见面板材-根据具体设计要求见设备特殊要求章节
Refer to the Particular specification for all exposed finished materials.
 - m. 冷媒介质-高温冰箱采用无 CFC 的环保雪种(R-290); 低温冰箱采用无 CFC 的环保雪种(R-290)
Refrigerant-CFC free, R-290 for refrigerators and R-290 for freezers.
 - n. 照明-由室内设计和灯光顾问指定, 见设备特殊要求章节。
Lights-to be specified by I.D. and lighting consultant. Refer to the Particular specifications.
- (本章节完) End